



Gimbal – Cardanically adjustable

Recessed spotlight with a compact high-precision swivel mechanism

Gimbal suspension is widely prevalent in technology and is a concept that is as old as Leonardo da Vinci, who suggested its use for nautical compasses. In lighting technology, gimbals are an elegant solution for pinpoint adjustment of the luminaires. Gimbal recessed spotlights transform this principle into the era of digital lighting – with a highly precise and convenient swivel mechanism in a compact design that stands apart from conventional approaches and enables

shallow recess depths. Different sizes and wattages for the full spectrum of light distributions make Gimbal ideal as a system for differentiated lighting design with focus on the high-contrast presentation of objects. With its unique technoid appearance in the ceiling, Gimbal lends itself perfectly to retail projects as well as to museums and other public buildings.



Structure and characteristics

The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website.

1 ERCO Spherolit lens

- Light distributions: narrow spot, spot, flood, wide flood, extra wide flood, oval flood or wallwash
- Oval flood 360° rotation

2 ERCO LED-module

- High-power LEDs: warm white (2700K or 3000K) or neutral white (3500K or 4000K)
- Collimating lens made of optical polymer

3 Mounting ring

- Covered mounting detail
- Fixing for ceiling thicknesses of 1–25mm (size 4) or 1–30mm (size 5–7)
- Polymer, white
- For flush mounting: mounting ring to be ordered separately, fixing for ceiling thicknesses of 12.5–25mm

4 Luminaire

- Black
- Cast aluminium, powder-coated
- Gimbal suspension: polymer
- 0°–40° tilt

5 Control gear

- Switchable, phase dimmable, DALI dimmable or Casambi Bluetooth
- Phase dimmable version: Dimming with external dimmers possible (trailing edge)

Variants on request

- Connection: 3- or 5-pole plug with connection cable (Wago or Wieland)
 - Housing: 10,000 further colours
- Please contact your ERCO consultant.



Design and application:
www.erco.com/gimbal-r

Gimbal Recessed spotlights



Oval flood freely rotatable
With luminaires with round light emission, the oval flood Spherolit lens can be freely rotated to align the light optimally to various objects.



Cardanic suspension
Especially with high ceilings, small swivel movements have a strong effect on the position of the light beam - cardanic suspension facilitates precise luminaire alignment in such cases.



Covered or flush mounting detail
As standard, all recessed luminaires have overlapping installation details. Flush mounting rings are available as accessories.



Shallow recess depth
In compact installation situations, every millimetre is decisive with the recess depth of a luminaire. ERCO has thus developed special luminaires for shallow recess depths that guarantee very good quality of light even in very tight installation conditions.

Special characteristics	
	Oval flood, freely rotatable
	Gimbal suspension
	Flush or covered mounting detail
	Shallow recess depth

	ERCO high-power LEDs
	Efficient Spherolit technology
	Different light distributions
	Different light colours


	Excellent thermal management
	EMC-optimised
	Various construction sizes
	Pivotable through 40°
	Tool-free mounting
	Accessory for maximum visual comfort

	Switchable
	Phase dimmable
	DALI dimmable
	Casambi Bluetooth

Gimbal Recessed spotlights – Luminaire arrangement

Recessed spotlights

Narrow spot, Spot, Flood




Accentuation
Gimbal recessed spotlights accentuate artwork, products and architectural details effectively. The ideal angle of tilt (α) for this is around 30°. The object is modelled without distorting the effect as a result of excessive shadowing. It also prevents shadows cast by the observer.

Arrangement: $\alpha = 30^\circ$

Recessed floodlights

Wide flood, Extra wide flood, Oval flood




Washlighting
The ideal angle of tilt (α) for floodlighting objects with a long, square shape, e.g. pictures, sculptures or merchandise displays, is around 30°.

Arrangement: $\alpha = 30^\circ$

Recessed lens wallwashers


Wallwash



Wallwashing
For good longitudinal uniformity, the spacing (d) of Gimbal lens wallwashers may be up to 1.2 times the offset from the wall (a).

Arrangement: $d \leq 1.2 \times a$

Optimal wall offset and luminaire spacing values are indicated in the wallwasher tables on the product data sheets.



For uniform vertical illuminance, the distance (a) of Gimbal lens wallwashers from the wall should be around one third of the wall height (h). This results in an angle of tilt (α) of approx. 35°.



Arrangement: $a = 1/3 \times h$ bzw. $\alpha = 35^\circ$

Suncorp Discovery
Centre, Sydney.
Architecture:
Geyer, Sydney.
Lighting design:
Medland Engin-
eering, Sydney.
Photography:
Jackie Chan,
Sydney.



Gimbal Recessed spotlights, recessed floodlights, recessed wallwashers

Construction size



LED module Maximum value at 4000K CRI 82

6W/825lm	2W/275lm (Narrow spot)
10W/1230lm	3W/410lm (Narrow spot)

12W/1650lm	4W/550lm (Narrow spot)
19W/2460lm	6W/820lm (Narrow spot)

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

Light distribution

Recessed spotlights	Recessed floodlights
Narrow spot	Wide flood
Spot	Extra wide flood
Flood	Oval flood
Recessed lens wallwashers	
Wallwash	

Recessed spotlights	Recessed floodlights
Narrow spot	Wide flood
Spot	Extra wide flood
Flood	Oval flood
Recessed lens wallwashers	
Wallwash	

Control

	Switchable		DALI
	Phase dimmable		Casambi Bluetooth

	Switchable		DALI
	Phase dimmable		Casambi Bluetooth


Colour (housing)

	Black
	10,000 colours *







	Black
	10,000 colours *








Accessories





	Lenses		Concrete mounting enclosure		Compensation set
	Snoot		Mounting ring		Cover ring
	Cross-baffle		Spacer plate		
	Honeycomb anti-glare screen		Mounting plate for panelled ceilings		





24W/3300lm	8W/1100lm (Narrow spot)
38W/4920lm	13W/1640lm (Narrow spot)

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

Recessed spotlights	Recessed floodlights
 Narrow spot	 Wide flood
 Spot	 Extra wide flood
 Flood	 Oval flood
Recessed lens wallwashers	
 Wallwash	

 Switchable	 DALI
 Phase dimmable	 Casambi Bluetooth

	Black
	10,000 colours *

* available on request

Article numbers and planning data:
www.erco.com/016053

Design and application:
www.erco.com/gimbal-r





melissa®

BAJA EAST