




Skim – Downlights as flexible as spotlights

Cost-effectiveness, efficiency and visual comfort for dynamic work environments.

Skim luminaires for track combine the flexibility of spotlights with the visual comfort of downlights in an unusual product design. This makes them ideal for work environments which are frequently reorganised. The arrangement and alignment of Skim luminaires on track can be adapted at any time to modified office layouts. Different wattages, light distributions and control types offer new design possibilities – in offices, retail projects and public buildings.



Structure and characteristics

The features described here are typical of products in this range. Special versions may offer additional or varying features. A comprehensive description of the features of individual products can be found on our website.

1 ERCO lens system

- Made of optical polymer
- Light distributions: wide flood, extra wide flood or oval flood
- Oval flood 90° rotation

2 ERCO LED-module

- High-power LED: warm white (2700K or 3000K) or neutral white (3500K or 4000K)

3 Anti-glare cone

- White (RAL9002), black or silver
- Optical cut-off 30°
- Polymer

4 Housing

- White (RAL9002), black or silver
- Cast aluminium, powder-coated
- Rotatable through 360° on adapter

5 Control gear

- Switchable, phase dimmable+On-board Dim, DALI dimmable or Casambi Bluetooth
- Phase dimmable + On-board Dim version: Dimming with external dimmers (trailing edge) possible and rotary control for brightness control on the luminaire

6 ERCO 3-circuit adapter or ERCO DALI adapter

Variants on request

- Housing: 10,000 further colours
- Please contact your ERCO consultant.



Design and application:
www.erco.com/skim-t




Skim for track 220-240V











Suitable for office workstations
 ERCO develops luminaires with the specifications of good glare control and high visual comfort. UGR values are used as support for purely norm-referenced lighting. With downlights though this should not be carried out using 'blanket' values, but should be implemented according to the individual arrangement of luminaires in the room.





Oval flood freely rotatable
 The oval flood Spherolit lens can be freely rotated with round luminaire heads to optimally match the lighting to various objects.

Small luminaire dimensions
 Small luminaires are discreet and place the focus on the light itself. Compact luminaire dimensions are particularly advantageous with small rooms.

Special characteristics	
	For office workstation lighting from UGR 12.3
	Oval flood, freely rotatable
	Small luminaire dimensions

	ERCO high-power LEDs
	Efficient lens system
	Optical cut-off 30°
	Different light colours


	Excellent thermal management
	EMC-optimised
	Various housing colours
	Easy installation

	Switchable
	Phase dimmable + On-board Dim
	DALI dimmable
	Casambi Bluetooth

Skim for track 220-240V – Luminaire arrangement

Downlights

Wide flood, Extra wide flood



General lighting


As an approximate luminaire distance (d) between two luminaires, the height (h) of the luminaire above the working plane can be used. The intersecting beams produce excellent uniformity. The recommended offset from the wall is half the luminaire spacing.

Rough guide: $d \leq 1.5 \times h$

Application area: as ambient lighting in the room and as flexible illumination of office workspaces.

Downlights oval flood


Oval flood



Linear lighting

Mounted in a row, the oval beams generate linear illumination, for example for circulation areas in the office or for hallways. As an approximate luminaire distance (d) between two luminaires, 1.5 times the height (h) of the luminaire above the working plane can be used.


Rough guide: $d \leq 1.5 \times h$



Memocorp Office.
Architecture:
Girvan Waugh,
Sydney. Photograph:
Jackie Chan,
Sydney.

Skim for track 220-240V

Construction size 265mm



LED module
Maximum value
at 4000K CRI 82

12W/1650lm
17W/2160lm
19W/2460lm

Light colour

	2700K CRI 92		3500K CRI 92
	3000K CRI 92		4000K CRI 82
	3000K CRI 97		4000K CRI 92

Light distribution

Downlights	Downlights oval flood
Wide flood	Oval flood
Extra wide flood	

Control

Switchable	DALI
Phase dimmable + On-board Dim	Casambi Bluetooth

Colour (housing)

White	Silver
Black	10,000 colours *



* available on request

Article numbers and planning data:
www.erco.com/016730

Design and application:
www.erco.com/skim-t



